(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 16 June 2005 (16.06.2005)

PCT

(10) International Publication Number WO 2005/055455 A1

(51) International Patent Classification7:

H04B 1/707

(21) International Application Number:

PCT/IB2004/052570

(22) International Filing Date:

26 November 2004 (26.11.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 03104548.7


4 December 2003 (04.12.2003) EP

(71) Applicant (for AE, AG, AL, AM, AT, AU, AZ, BA, BB, BE, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CY, CZ, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, SZ, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW only): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

- (71) Applicant (for DE only): PHILIPS INTELLECTUAL PROPERTY & STANDARDS GMBH [DE/DE]; Steindamm 94, 20099 Hamburg (DE).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): HEINLE, Frank [DE/DE]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (74) Agents: ELEVELD, Koop, J. et al.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,

[Continued on next page]

(54) Title: STATION COMPRISING A RAKE RECEIVER



(57) Abstract: Stations like mobile terminals, bases stations and network nodes comprising rake receivers with fingers require relatively many calculations to be performed for despreading a symbol. By replacing despreading multipliers, integrators and dum pers in the fingers by Hadamard transformers (62), chips of several symbols with orthogonal channelization codes can be despreaded simultaneously, and the stati on and the rake receiver have become more efficient. The despreading section (60 of the finger (34) comprises the Hadamard transformer (62) and a serial-to-par allel converter (61) comprising downsamplers (71-73). The station is a high-spee d downlink packet access station (HSDPA) in a universal mobile telecommunication system (UMTS), with a number of de-channelization codes used being at least ten percent of a despreading factor used. For example, the despreading factor used is equal to sixteen, with the maximum possible number of de-channelization codes used being equal to five, ten or fifteen, depending on the capability class of the station.





WO 2005/055455 A1



TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE,

SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.